

Application No.
09/508,826
Response to Office Action

Customer No. 01933

Listing of Claims:

Claims 1-15 (Canceled).

16. (Currently Amended) A checking device for checking an operator of an apparatus, the checking device comprising:

image storage means for storing a check image for checking the operator;

5 registered data storage means for storing location data of a registered checking point set to the check image, the location data representing relative coordinates of the checking point with respect to an origin of the check image;

10 display means, having a display screen, for displaying the check image based on a preset location of display coordinates on the display screen;

attaining means for attaining coordinates of a point designated by the operator on the display screen;

15 detection means for detecting relative coordinates of the designated point on the check image displayed on the display screen based on the preset location of the display coordinates, from the coordinates attained by the attaining means;

20 comparison means for comparing the relative coordinates of the designated point detected by the detection means with the relative coordinates of the registered checking point represented

Application No.
09/508,826
Response to Office Action

Customer No. 01933

by the location data stored in association with the check image;
and

check control means for determining that the operator is
authorized to use the apparatus when a difference between the
25 relative coordinates of the registered checking point and the
relative coordinates of the designated point is within an
allowable range; and

update means for updating the display coordinates location,
which determines where the check image is displayed, such that
30 the location at which the check image is displayed is altered;
wherein when no designation is made by the operator on the
display screen on which the check image is displayed, the display
location of the check image is periodically altered.

Claims 17 and 18 (Canceled).

19. (Previously Presented) The checking device according
to claim 16, wherein:

the registered data storage means stores a display size of
the check image;

5 the display means displays the check image in a
predetermined display size; and

the comparison means compares (i) a ratio between the
relative coordinates of the designated point detected by the

Application No.
09/508,826
Response to Office Action

Customer No. 01933

detection means and the display size of the check image with (ii)
10 a ratio between the relative coordinates of the registered
checking point and the display size of the check image.

20. (Previously Presented) The checking device according
to claim 16, wherein:

a respective check image and a corresponding registered
checking point set to the check image are prepared for each one
5 of a plurality of programs, and are stored in the image storage
means and in the registered data storage means according to the
corresponding one of the plurality of programs; and

when any of the plurality of programs is activated, the
corresponding check image is selected for display, and checking
10 of the designated point is performed based on the registered
checking point corresponding to the activated program.

21. (Currently Amended) A computer-readable recording
medium which stores a program for controlling a computer to
perform the steps of:

storing location data of a registered checking point which
5 is set to a check image in registered data storage means, the
location data representing relative coordinates of the registered
checking point with respect to an origin of the check image;

displaying the check image on a display screen based on a

Application No.
09/508,826
Response to Office Action

Customer No. 01933

preset location of display coordinates;

10 attaining coordinates of a point designated by an operator
on the display screen;

15 detecting relative coordinates of the designated point on
the check image displayed on the display screen based on the
preset location of the display coordinates, from the attained
coordinates;

20 comparing the detected relative coordinates of the
designated point with the relative coordinates of the registered
checking point stored in association with the check image; ~~and~~
determining that the operator is an authorized operator when
a difference between the relative coordinates of the designated
point and the relative coordinates of the registered checking
point is within an allowable range; ~~and~~

25 updating the display coordinates location, which determines
where the check image is displayed, such that the location at
which the check image is displayed is altered;

wherein when no designation is made by the operator on the
display screen on which the check image is displayed, the display
location of the check image is periodically altered.

22. (Currently Amended) A checking device for checking an
operator of an apparatus, comprising:

Application No.
09/508,826
Response to Office Action

Customer No. 01933

image storage means for storing a check image used for
checking the operator;

5 registered data storage means for storing location data of a
registered checking point set to the check image, the location
data representing relative coordinates of the registered checking
point with respect to an origin of the check image, and for
storing a display size of the check image;

10 display means, having a display screen, for displaying the
check image based on a preset location of display coordinates on
the display screen in a predetermined display size;

attaining means for attaining coordinates of a point
designated by the operator on the display screen;

15 detection means for detecting relative coordinates of the
designated point on the check image displayed on the display
screen based on the preset location of the display coordinates,
from the coordinates attained by the attaining means;

comparison means for comparing (i) a ratio between the
20 relative coordinates of the designated point detected by the
detection means and the display size of the check image with
(ii) a ratio between the relative coordinates of the registered
checking point and the display size of the check image; and

check control means for determining that the operator is
25 authorized to use the apparatus when a difference between the two
ratios is within an allowable range; and

Application No.
09/508,826
Response to Office Action

Customer No. 01933

update means for updating the display size of the check
image, such that the display size of the check image is altered;
wherein when no designation is made by the operator on the
30 display screen on which the check image is displayed, the display
size of the check image is periodically altered.

Claims 23 and 24 (Canceled).

25. (Currently Amended) A computer-readable recording
medium which stores a program for controlling a computer to
perform the steps of:

5 storing location data of a registered checking point which
is set to a check image, the location data representing relative
coordinates of the registered checking point with respect to an
origin of the check image, and storing a display size of the
check image;

10 displaying the check image in a predetermined display size
on a display screen based on a preset location of display
coordinates;

attaining coordinates of a point designated by an operator
on the display screen;

15 detecting relative coordinates of the designated point on
the check image displayed on the display screen based on the

Application No.
09/508,826
Response to Office Action

Customer No. 01933

preset location of the display coordinates, from the attained coordinates;

20 comparing (i) a ratio between the detected relative coordinates of the designated point and the display size of the check image with (ii) a ratio between the relative coordinates of the registered checking point and the display size of the check image; and

25 determining that the operator is an authorized operator when a difference between the two ratios is within an allowable range; and

updating the display size of the check image, such that the display size of the check image is altered;

30 wherein when no designation is made by the operator on the display screen on which the check image is displayed, the display size of the check image is periodically altered.